

Improving the Simplified Ventilation Model for Mine Expansion Planning at Kiruna Mine

Ventsim User Conference 2023

Tata Fritsco Mabui, Research Engineer

Agenda

- Introduction
- Previous and current work
- Progress and procedure examples
- Current results
- Next steps
- Summary

Introduction

LKAB


- Swedish state-owned company, established in 1890
- Major European producer of iron ore products
- Three different mines above the arctic circle (Kiruna, Malmberget, Svappavaara)
- Undergoing ambitious transformation towards
 - Critical minerals
 - Carbon-free sponge iron
 - A new world standard for mining operations



Introduction – Kiruna Mine


- Kiruna Mine is the world's largest underground iron ore mine
- Sublevel caving method
- Orebody length 4-5 km with width of up to 120 m
- Current production below level 1000 m with main haulage level at the depth of 1365 m
- Production roughly 28 Mtpa

Kiruna Mine system.




Introduction – Primary ventilation system

- Push-pull system
- Majority of the main fans located on the surface
- Total installed ventilation capacity around 2500 m³/s
 - Most stations have capacity of 150 m³/s, which is used to supply fresh air to one mining block
 - The largest station has capacity of 450 m³/s to supply two blocks
- About 15 % of the supplied airflow is used to supply permanent infrastructure while most of the fresh air is distributed to production areas



Simplified ventilation model building – Previous work

- Creating a model to study airflow requirements for the Kiruna mine expansion towards greater depth and optimizing the current ventilation system
- A simplified model was used to do the first ventilation model calibration



Simplified ventilation model building – Previous work

Input

- Old mine maps from Microstation + Deswik files (for completion of the upper levels)
- Deswik files
- Existing Ventsim model for Block 4 and Block 8
- Existing Ventsim model for the hoist area

Include (+)

- In-use ventilation shafts, production shafts and ore passes, ramps, footwall drifts, transportation and medial levels
- Main fans and ventilation walls
- Known orifices and regulators in ventilation walls

Exclude (-)

- Production drifts
- Auxiliary fans and ducts
- Old ventilation shafts
- Konsuln test mine
- Level, block, airway separation
- Upper levels area (levels, ramps)
- Old connections between hoist area and main mine


Simplified ventilation model building – Previous work

Outcome

- Airflow in primary ventilation infrastructure was found to correlate to a decent extent (within +/- 10%)
- Leakage into cave levels and from old ventilation shafts, causing erroneous airflow and discrepancies between measured values
- Missing connections between the hoist area and the main mine affected the airflow distribution in the model (e.g., too high airflows in the few connections)

New objective


- Necessity of more detailed model to improve the accuracy of the results and to assist in near-future planning



Updated ventilation model building

Input

- Previous model
- Deswik files
- Actual old level references
- Updated main ventilation routes
- Actual airway profile sizes




Include (+)

- All existing airways from the previous model
- Additional airways (ramps, levels, and other previously excluded connections)
- Old shafts
- Actual regulators (walls, doors, known orifices)
- Upper-level areas
- Old connections between the hoist area and the main mine

Exclude (-)


- Production drifts
- Auxiliary fans and ducts
- Old ventilation shafts without level connections, especially on the uppermost level
- Konsuln test mine

Ventilation model building process – Current status






Ventilation model building process – Improvements

- Organizing the model based on functionality, such as creating new airway types, mining blocks, and level separation
 - Improve usability of the model
- Performing site visits to confirm or correcting airways based on old, inaccurate references
 - Reduce erroneous airflow distribution
- Adding previously excluded old tunnel sections and levels as well as recent developments
 - Better represent the current airflow circuits




Ventilation model building process – Improvements


- Adding resistances (e.g., doors, regulators) into the ventilation model
- Updating of standard airway dimensions to actual profiles



Default 3D tunnel profile



Actual tunnel profile




Updated 3D tunnel profile

Ventilation model building process – Improvements

- Airflows disturbed by added relevant infrastructure, lowering model accuracy
- Limited resources, information, and accessibility of the area often required assumptions to be made
 - Assumptions based on available information and field work
- Accuracy of modelled airflows improved



Type of blockage between the old shafts and its connection




Before closing the shaft connection



After applying resistance


Model update results and discussion

- Airflow measurements were performed at several points used for previous model calibration
- Results were compared with model values of the previous and updated model
- Overall, considering the added infrastructure, an improvement was observed
- Current model shows better results with roughly 73% level of inaccuracy compared to previous model measurement




Model update results and discussion – Example

- Previously, the model showed high flow in the airway connections between the main mine and the mine hoist – affecting the overall airflow in the model
- Observed reduction to 37% average error after updates performed





Model update results and discussion

- Airflow quantity of the updated model and the measurement still have some big value gaps
- For the upper parts, no conclusion due to the lower number of taken data



Challenges

- New added main ventilation routes cause high differences in values
- New added blockage information could potentially create high discrepancy, which leads to inadequate airflow distribution
- Absence of auxiliary fans was recognized as a main contributor for high-value differences
- Assumed upper-level sections could bring the imbalance into the model as well
- Time gap between the change in infrastructure and documentation can cause missing airways that lead to an inaccurate model



Further work

1

Inclusion of
secondary fans and
footwall drift ducts

2

More accurate
evaluation of
resistance values

3

Taken more detailed
information from
upper-level

4


Continue mine
ventilation mapping
to find blockages for
proper airflow
distribution

5

Continue updating
the airways

Summary

- The level of detail of the previous Kiruna mine ventilation model was increased
 - More detailed parameters were used (e.g. old shafts, upper-level areas, and other previously excluded connections)
 - Adjusting the model based on the available information (e.g. Deswik files actual airway profile size) and the findings through fieldwork (e.g. blockages)
- The usability of the model was improved
 - The model is now organized based on functionality (airway types, mining blocks, and level separation)
 - Changes are available in the model
 - Overall, the discrepancy between measured and modelled airflows is still high, but improvements have been observed
- Continued work to further strengthen the model



Any questions?



©Tata Fritsco Mabui

**Thank you for your
attention**